



HV400



K34R<sub>8</sub>-L8

Valve

- J4V
- J4V100
- J4V200
- J4V300
- J4V400
- 5V
- Manifold
- JSY
- 5JV
- MCS
- JVT307
- JEL
- MVSD
- VF
- BM
- NAMUR
- 551
- JEL10
- 3VJZF
- Diaphragm
- JELVD
- 3V1
- Coil
- 2P
- 2V
- 2W
- 2W(Big)
- 2L
- VX
- PU
- PU225
- 2Q
- JEL5404
- JEL6213
- BU
- Pulse
- JELJZF
- 4H
- TSV
- MPV
- 4HV
- HV, K**
- 4R
- 4F210
- FV
- MSV
- JM
- ASC, RE
- QE, QEA
- ST
- HSV

## Ordering Code

<b>HV</b>	<b>400</b>	<b>02</b>	<b>B</b>
Specification	Series	Port Size	Connection type
Hand Switching Valve		02: G1/4" 03: G3/8" 04: G1/2"	Blank: Threaded B: Sub-plated

<b>K</b>	<b>34</b>	<b>R<sub>8</sub></b>	<b>L8</b>
Specification	Series	Port Size	Connection Type
Hand Switching Valve	24: 4/2 Way 34: 4/3 Way	R <sub>8</sub> : Hand Switching Valve	L6: G1/8" L8: G1/4"

## Specification

Model	HV400-02	HV400-03	HV400-04	K34R <sub>8</sub> -L6	K34R <sub>8</sub> -L8
Working Medium	40 Micron Filtered Air				
Port Size	G1/4"	G3/8"	G1/2"	G1/8"	G1/4"
Effective Cross Section Area	30 mm <sup>2</sup> (CV=1.68)			18 mm <sup>2</sup> (CV=1.00)	
Working Pressure	0 ~ 0.8 MPa				
Max. Ambient Temperature	-20 ~ 70°C				

## Overall Dimension

