



PU225-04-J



PU225-06-J



PU225-08-J



SPU225-06-J




SPU225-20-J

Ordering Code

| PU | 225 | 03 | A | AC220V | J |
|--|-----------------------|--|---------------------------------------|------------------------------------|--|
| Specification | Operation | Port Size | Fix Form | Standard Voltage | Wiring |
| PU : 2/2 way SPU : 2/2 way Stainless steel | 225: Internal piloted | 03: 3/8" 04: 1/2" 06: 3/4" 08: 1" 12: 1 1/4" 14: 1 1/2" 20: 2" | A: Standard type F: Flange install | AC220V AC110V DC12V DC24V | J: Terminal W: Lead wire T: Coil with time |


Symbol



Specification

| Model | PU225-03A | PU225-04A | PU225-06A | PU225-08A | PU225-12A | PU225-14A | PU225-20A |
|---------------------------|------------------|------------|------------|------------|------------|------------|-----------|
| | SPU225-03A | SPU225-04A | SPU225-06A | SPU225-08A | SPU225-12A | SPU225-14A | |
| Working Medium | Air, Water, Oil | | | | | | |
| Operation | Internal Piloted | | | | | | |
| Type | Normal Close | | | | | | |
| Orifice | 13mm | 13mm | 25mm | 25mm | 38mm | 38mm | 50mm |
| CV Value | 4.50 | 4.50 | 12.00 | 12.00 | 22.00 | 30.00 | 48 |
| Port Size | 3/8" | 1/2" | 3/4" | 3/4" | 1 1/4" | 1 1/2" | 2" |
| Medium of Body | Brass or Steel | | | | | | |
| Operation Fluid Viscosity | Below 50 CST | | | | | | |
| Working-pressure | 0.05 ~ 1.0 MPa | | | | | | |
| Max. Test Pressure | 1.5 MPa | | | | | | |
| Ambient Temperature | -10 ~ 80 °C | | | | | | |

Overall Dimension



Dimension

| Model | Bore | A | B | C | Model | Bore | A | B | C |
|------------|--------|----|-------|----|------------|----------|-------|-----|-----|
| PU225-03A | PT3/8" | 66 | 106 | 48 | PU225-12A | PT1 1/4" | 127 | 140 | 95 |
| SPU225-03A | PT3/8" | 66 | 106 | 48 | SPU225-12A | PT1 1/4" | 127 | 140 | 95 |
| PU225-04A | PT1/2" | 66 | 106 | 48 | PU225-14A | PT1 1/2" | 127 | 140 | 95 |
| SPU225-04A | PT1/2" | 66 | 106 | 48 | SPU225-14A | PT1 1/2" | 127 | 140 | 95 |
| PU225-06A | PT3/4" | 75 | 112 | 58 | PU225-20A | PT2" | 160.5 | 159 | 114 |
| SPU225-06A | PT3/4" | 75 | 112 | 58 | | | | | |
| PU225-08A | PT1" | 97 | 124.5 | 70 | | | | | |
| SPU225-08A | PT1" | 97 | 124.5 | 70 | | | | | |

Valve

- J4V
- J4V100
- J4V200
- J4V300
- J4V400
- 5V
- Manifold
- JSY
- 5JV
- MCS
- JVT307
- JEL
- MVSD
- VF
- BM
- NAMUR
- 551
- JEL10
- 3VJZF
- Diaphragm
- JELVD
- 3V1
- Coil
- 2P
- 2V
- 2W
- 2W(Big)
- 2L
- VX
- PU
- PU225**
- 2Q
- JEL5404
- JEL6213
- BU
- Pulse
- JELJZF
- 4H
- TSV
- MPV
- 4HV
- HV, K
- 4R
- 4F210
- FV
- MSV
- JM
- ASC, RE
- QE, QEA
- ST
- H5V